China Print Supplies

EPSON SERIES i3200 / i1600
DTF Garment Printer



2 / 3 / 4 Printheads

Variable Dot

CMYK
CMYKFoFgFyFp
CMYKRGOB

High Density White,
Automatic
Powder Collection

chinaprintsupplies.co.uk

DTF Garment Printer



8 Colour option for excpetionally vibrant, rich colours and wide colour gammut,



- Industry Leading Rip Software
- Knock me out black
- Inteligent white production.

DigitalFactory 11
DesignPro Edition





Up to 8 channels of white for high density white printing

DTF Garment Printer | DTF-400D & DTF-400S

Features



Compact Integrated Design

Compact and elegant design, strong , space saving, easy operation, provides high accuracy, consitent output.



High Quality Components

Branded accessories such as Hiwin guide rail, Italian Megadyne belt are used for high attrition area, with single piece aluminum beam, greatly increased precision, stability and lifetime of the machine.



Integrated Control Centre

Convenient and high-efficiency.



Anti-collision System

Printer will automatically stop when the printhead carriage hits any unexpected object during working, and the system memory function supports continuing printing from the interruption, reducing material waste.



Multifunctional Machine for Mass Production

Apply to different fabric include cotton, polyester, nylon, denim, etc. Makes mass production of DIY t-shirts, hoodies, sportswear, pants, canvas bag quick and easy.

Specification

Model No.		DTF-400D	DTF-400S
Printhead		2 × Epson i1600	2 × Epson i3200
Resolution		2400dpi	2400dpi
Ink Color		CMYK + W	
Media	Size	40cm	
	Types	PET Film	
Speed	Draft	7 m^2/h	11 m^2/h
	Standard	4 m^2/h	6.5 m^2/h
Ink Type		Pigment Ink	
Application		DIY Printing On T-shirt, Hoodies, Cap, Bag, Etc.	
Ink Droplet		1.5-21pl Variable	
Powder Shaking And Heating		Standard Equipped	
Cleaning		Automatic Cleaning, Anti-Clogging Flash Function & Capping System	
Feed & Take Up		Automatic Media Feeding (Standard) & Take Up System (Standard)	
Environment		Temperature: 20-28℃, Humidity: 40%-60%	
Rip Software		FlexiPrint (Standard) / Digital Factory (Optional)	
Interface		USB 3.0	
Power		AC 110/ 220V, 50/ 60Hz, 3400W	

Specifications are subject to change without notice.

DTF Garment Printer | DTF-600 Series & DTF-800 Series

Features



Compact Integrated Design

Compact and elegant design, strong , space saving, easy operation, provide high accuracy output. Not only one partner for your printing business, but also a decoration for the company.




High Quality Components

Branded accessories such as Hiwin guide rail, Italian Megadyne belt are used for high attrition area, with the one time molding aluminum beam, greatly increased the precision, stability and lifetime of the machine.

Standard Auto Powder Collecting & Re-using

Auto Powder Collecting & Re-using supported by mechanical spiral structure. Is labour saving, and greatly increase the working efficiency.



Anti-collision System

Printer will automatically stop when the printhead carriage hits any unexpected object during working, and the system memory function supports continuing printing from the interruption part, reducing the material waste.



Multifunctional Machine for Mass Production

Apply to different fabric include cotton, polyester, nylon, denim, etc. Make the mass production of DIY t-shirts, hoodies, sportswear, pants, canvas bag to be convient.

Specification

Model No.		DTF-600D	DTF-600S	DTF-800D	DTF-800S
Printhead		2/3/4 Epson i1600	2/3/4 Epson i3200	2/3/4 Epson i1600	2/3/4 Epson i3200
Resolution		2400dpi	2400dpi	2400dpi	2400dpi
Ink Color		CMYK+W Optional Red Green Orange & Blue, Flourescent M,Y,O,G			
Media	Size	60cm		80cm	
	Types	PET Film			
Speed	Draft	8 m^2/h (2 heads)	19 m^2/h (4 heads)	9 m^2/h (2 heads)	21 m^2/h (4 heads)
	Standard	4.5 m^2/h (2 heads)	9.5 m^2/h (4 heads)	5 m^2/h (2 heads)	11.5 m^2/h (4 heads)
Ink Type		Pigment Ink			
Application		DIY Printing On T-shirt, Hoodies, Cap, Bag, Etc.			
Ink Droplet		1.5-21pl Variable			
Powder Shaking And Heating		Standard Equipped			
Powder Collecting And Re-using		Standard			
Built-in Smoke Filter		Optional			
Cleaning		Automatic Cleaning, Anti-Clogging Flash Function & Capping System			
Feed & Take Up		Automatic Media Feeding (Standard) & Take Up System (Standard)			
Environment		Temperature: 20-28℃, Humidity: 40%-60%			
Rip Software		FlexiPrint (Standard) / Digital Factory (Optional)			
Interface		USB 3.0			
Power		AC 110/ 220V, 50/ 60Hz, 3400W			

Specifications are subject to change without notice.